

Rtd Process Style

Class 102 – Moderate, High and Full Temp Range

RTDS

Capsule Rtd PLUG AND JACK CONNECTOR

102 Rtd Process Style, Capsule Configuration, Plug and Jack Connector								
Code	Temperature Range							
M	Moderate Temp Range = -50 to 250C (-58 to 482F)							
H	High Temp Range = -50 to 500C (-58 to 932F)							
F	Full Temp Range = -200 to 500C (-328 to 932F)							
Code	Accuracy							
P2A	Platinum, 100 Ohms ±.06%, .00385 Temperature Coefficient							
P2B	Platinum, 100 Ohms ±.12%, .00385 Temperature Coefficient							
P2C	Platinum, 100 Ohms ±.5%, .00385 Temperature Coefficient							
Code	Element Configuration							
3S	Three Wire Single							
Code	'L' Sheath Length							
000	Specify Length in inches (example: 125 = 12.5 inches) Note: Minimum 1.5" and Maximum 36"							
Code	'D' Sheath Diameter							
A	1/8" Diameter					M Only		
B	3/16" Diameter					M Only		
C	1/4" Diameter (Standard Plug and Jack Sizes Only)							
Code	Connector Options							
1	Plug							
2	Jack							
3	Plug and Jack							
4	Miniature Plug							
5	Miniature Jack							
6	Miniature Plug and Jack							
Code	Pin Style							
H	Hollow (Standard)							
S	Solid							
F	Miniature Flat Solid							
102	M						Enter Desired Part Number Here	
102	M	P2B	3S	125	B	1	H	Example Part Number

