

RTD Motor/Generator Style Class 302

Stator Rtd PADDLE, LAMINATED

302 Stator Rtd, Paddle, Laminated							
Code		Classification					
F		Class F; 155C Maximum Temperature Limit, Epoxy glass Insulation Dielectric Strength 3,000 volts					
Code		Accuracy					
P2B		Platinum, 100 Ohm +/- .12% at 0C, .00385 temperature coefficient					
P2D		Platinum, 100 Ohm +/- .2% at 0C, .00385 temperature coefficient					
P2C		Platinum, 100 Ohm +/- .5% at 0C, .00385 temperature coefficient					
C1D		Copper, 10 Ohm +/- .2% at 25C, .00427 temperature coefficient					
Code		Element Configuration					
3S		Three wire single (color code: red/white(2))					
3D		Three wire dual (color code: red/white(2)/blue/yellow(2))					
4D		Four wire (total) dual (color code: red(2)/white(2)/blue(2)/yellow(2))					
Code		'L' Leadwire Length					
000		Specify in Inches (example: 120 = 120 Inches)					
Code		Lead Option					
A		Leadwire Only					
B		Leadwire with cable					
Code		Leadwire Termination					
1		Stripped and Tinned					
2		1" Staggered with Butt Splice					
302	F						Enter Desired Part Number Here
302	F	P2C	3S	072	B	1	Example Part Number

Motors

