

HVAC Rtd's Class 510M – Moderate Temp Range

Averaging Rtd BENDABLE GENERAL PURPOSE

510 HVAC Rtd, Averaging, Bendable General Purpose								
Code		Temperature Range						
M		Moderate Temp Range = -50 to 250C (-58 to 482F)						
Code		Accuracy						
P2B		Platinum, 100 Ohms ±.12%, .00385 Temperature Coefficient						
P2C		Platinum, 100 Ohms ±.5%, .00385 Temperature Coefficient						
Code		Element Configuration						
2S		Two Wire Single (color code: red/white)						
3S		Three Wire Single (color code: red(2)/white)						
4S		Four Wire Single (color code: red(2)/white(2))						
Code		'L' Sheath Length						
0000		Specify in Inches (example: 1500 = 1500 inches) Minimum 6" and Maximum 1800"						
Code		'M' Sheath Material						
A		316 Stainless Steel (50' Max. Length)						
B		Aluminum						
C		Copper						
Code		Additional Options						
N		No Options						
W		Leadwire Options						
510		M						Enter Desired Part Number Here
510	M	P2B	3S	0120	A	W	Example Part Number	

Sensitive Length = L - 4"

See Leadwire Configuration Section for Lead Options		
Typical Catalog number with leadwire options.		
510MP2B3S125AW	/	670000A004A
Catalog Number		Leadwire Option Code



Lengths greater than 6 feet are shipped in 30" diameter coils.

